




产品参数	BZ-65C	BZ-85C	BZ-105C	BZ-120C
出力:	60kN	60kN	150kN	150kN
行程:	50mm	50mm	70mm	70mm
剪切范围:	Φ65mm (铜铝线)	Φ85mm (铜铝线)	Φ105mm (铜铝线和铠装线缆)	Φ120mm (铜铝线和铠装线缆)
电池电压/电容:	18v/4.0Ah	18v/4.0Ah	18v/5.0Ah	18v/5.0Ah
充电时间:	80分钟	80分钟	100分钟	100分钟
<b>配件</b>				
电池:	2块	2块	2块	2块
充电器:	1个	1个	1个	1个
油缸密封圈:	1套	1套	1套	1套
安全阀密封圈:	1套	1套	1套	1套



铜铝线 ✓



钢芯铝绞线 ×



铠装电缆 ✓



钢筋 ×



产品参数	BZ-55
出力:	120kN
行程:	58mm
液压油:	壳牌得力士 S2V HV15
剪切范围:	≤Φ55mm
铠装电缆:	≤Φ55mm
钢芯铝绞线:	≤Φ52mm
铜铝电缆:	≤Φ55mm
碳钢圆棒:	≤Φ20mm
钢绞线:	≤Φ20mm
钢丝线:	≤Φ25mm
产品尺寸:	452x360x83mm
电池电压/电容:	18V/4.0Ah
充电时间:	80分钟
包装箱:	塑料箱
重量:	
<b>配件</b>	
电池:	2块
充电器:	1个
油缸密封圈:	1套
安全阀密封圈:	1套

