



| HD-14L | |
|--------|-----------------------|
| 技术参数 | |
| 适用范围: | 非绝缘端子 |
| 压接范围: | 5.5-14mm ² |



| HD-16L | |
|--------|------------------------|
| 技术参数 | |
| 适用范围: | 非绝缘端子 |
| 压接范围: | 1.25-16mm ² |



| HD-25L | |
|--------|-----------------------|
| 技术参数 | |
| 适用范围: | 非绝缘端子 |
| 压接范围: | 5.5-25mm ² |



| HD-50L | |
|--------|-----------------------|
| 技术参数 | |
| 适用范围: | 非绝缘端子 |
| 压接范围: | 5.5-50mm ² |

套装工具 (压同轴线缆端子)
五副模具



T05H-5A

T03C-5D

| 技术参数 | | | | | | | | |
|---------|---|--------|--------|-------|--------|----|---------|-----------------------------------|
| 型号 | | | | | | 类型 | 型号 | 压接范围 |
| AN-02H | 6.5mm | 5.4mm | | | 1.72mm | | AN-10 | 1.5-6mm ² 非绝缘端子 |
| | 55,58,59,62,140,141,142,223,303,400,FIBER OPTIC,BELDEN 8279 | | | | | | | |
| AN-02H1 | 6.5mm | 5.4mm | 3.25mm | 2.0mm | 1.72mm | | AN-03B | 1.0-4mm ² 非绝缘开放式插塞型连接头 |
| | 58,59,62,8X,140,141,174,210,223,303,400,FIBER OPTIC,BELDEN 8279 | | | | | | | |
| AN-05H | 8.1mm | 6.5mm | 5.4mm | | 2.6mm | | AN-04WF | 1.0-6mm ² 套管式端子 |
| | 55,58,59,62,5,6,21,140,141,142,143,210,223,303,400,BELDEN 8279,8281,9231,9141 | | | | | | | |
| AN-1741 | 4.5mm | 3.25mm | 3.84mm | 2.0mm | 1.72mm | | AN-16WF | 6-16mm ² 套管式端子 |
| | 122,174,178,180,187,188,195,316,FIBER OPTIC,BELDEN8218 | | | | | | | |
| AN-457 | 11mm | 8.2mm | 5.4mm | | | | AN-03C | 0.5-6mm ² 预绝缘端子 |
| | 4C,5C,7C,CABLE | | | | | | | |